



Phase Change Material

Application

savENRG® AMBIENT Packs are designed for overheat protection and maintaining product temperature below 25°C (75°F) during transportation.

Instructions:

1. Set the refrigerator setting to 15°C (60°F). Place the AMBIENT Packs flat on a metal tray. Check for leaks while the packs are in a liquid state. Dispose of any leaky packs.
2. Position the tray in the refrigerator. Multiple trays can be conditioned at the same time, as long as there is adequate and unblocked air flow over the surface of the AMBIENT Packs.
3. Allow the AMBIENT Packs to charge for at least 24 hrs before use. The AMBIENT packs must feel completely solid after conditioning.
4. The pack-out and labeling operations should be executed in a controlled room temperature environment.
5. After pack-out, leave the shipping boxes in the temperature-controlled room until they are ready for pick up.

CAUTION

DO NOT boil the AMBIENT Packs.

DO NOT microwave or flash freeze the AMBIENT Pack. Excessive heating or cooling can lead to over expansion or contraction of the product and may damage the AMBIENT Pack.

Take additional caution while handling the conditioned AMBIENT Packs.

DO NOT drop the pack after conditioning as the impact may damage the AMBIENT Pack.

HANDLE GENTLY WITH CARE AND DO NOT SQUEEZE. Check for leaks when the packs are in a liquid state. Dispose of any leaky packs as per instructions. This product is water based with a mixture of salts. It is non-toxic and non-flammable. Please refer to the product SDS for detailed instructions on disposal.

RGEES, LLC

170 Bradley Branch Rd., Suite # 6, Arden, NC, 28704

Tel: +1.828.708.7178 E-mail: info@rgees.com WEB: www.rgees.com

© 061720-4